

THE PURPOSE OF THIS KIT IS TO REMOVE THE MATERIAL IN EXCESS FROM THE FACTORY OEM SHOCK SHAFT ON THE KYB AND SHOWA SHOCKS.

SHAFT TOOL KIT COMPOSITION:

THE KIT IS DELIVERED WITH TWO DIFFERENT TOOL DIMENSIONS, 14 mm AND 20 mm. BOTH OF THEM WITH AN INNER PIN AS A CENTERING PURPOSE.

BASED ON THE SHOCK TYPE, THERE ARE THE DIFFERENT CONNECTIONS BETWEEN THE SHAFT TOOL AND THE INNER PINS.



KYB SHOCK TOOL
CONFIGURATION 12 mm
SHIMS

USE THE 14 mm MILL
TOOL WITH 5.00 mm INNER
PIN



SHOWA SHOCK TOOL
CONFIGURATION 12 mm
SHIMS

USE THE 14 mm MILL TOOL
WITH 3.60 mm INNER PIN



SHOWA SHOCK TOOL
CONFIGURATION 16 mm
SHIMS

USE THE 20 mm MILL TOOL
WITH 3.60 mm INNER PIN

RIGHT WORKING RPM:

- 14 mm 430 RPM
- 20 mm 320 RPM